2025/11/29 09:52 1/1 batterycomparison

This page contains comparison of different batteries to be used for Ise01 LoRaWAN Soil Moisture Sensor.

Battery Voltage description: The battery for the lse01 should be between 3.0V to 3.6V. If we need to use a battery less than 3.3 volts we have to remove diode D1 and shortcut the two pads of it.Diode D1 lays between the main circuit and the battery If battery is less than 2.7 volts user have to replace the battery.

Specific power and Specific energy are important factors to keep in mind before choosing a battery.

Specific energy: defines the battery capacity in weight (Wh/kg). The capacity relates to the runtime. **Specific power:** It's the ability to deliver a high current and indicates loading capability.

	Current	Voltage	Cost	Charge cycle	Lifespan	Safety	Specific Power		Thermal runaway	C rate
Lithium Thino- Chloride										
Nickle Manganese Cobalt Oxide	mA	3.60V, 3.70V nominal;typical operating range 3.0-4.2V/cell, or higher	Low	1000-2000	Moderate	Moderate	Moderate	High	210°C	
Lithium Iron Phosphate		3.20, 3.30V nominal; typical operating range 2.5-3.65V/cell	Low	2000 and higher	High	High	High	Low	270°C (518°F) Very safe battery even if fully charged	
Lithium Titanate		2.40V nominal; typical operating range 1.8-2.85V/cell	High	3,000-7,000	High	High	Moderate	Low	One of safest Li- ion batteries	1C typical; 5C maximum, charges to 2.85V
Lithium-lon Polymer			Low		Low	Low				
NiMH										

References:

http://wiki.dragino.com/xwiki/bin/view/Main/User%20Manual%20for%20LoRaWAN%20End%20Nodes/LSE01-LoRaWAN%20Soil%20Moisture%20%26%20EC%20Sensor%20User%20Manual/https://owlcation.com/stem/Comparing-6-Lithium-ion-Battery-Types

From:

https://student-wiki.eolab.de/ - HSRW EOLab Students Wiki

Permanent link:

https://student-wiki.eolab.de/doku.php?id=eolab:treemap:batterycomparison&rev=1659108106

Last update: 2023/01/05 14:38

