

# Deploy Jitsi with Docker + High Quality

here is codeEvery eolab.de has to be changed to your URL.

## Prerequisites

- Ubuntu Server 20.04
- Docker and Docker-Compose are installed
- Running NGINX Reverse Proxy
- A SSL certificate for the desired url

## Downloading Jitsi

1. `git clone https://github.com/jitsi/docker-jitsi-meet.git`
2. `mv docker-jitsi-meet/ jitsi-meet/`
3. `cd jitsi-meet/`
4. `cp env.example .env`
5. `./gen-passwords.sh`
6. `mkdir -p ~/.jitsi-meet-cfg/{web/letsencrypt,transcripts,prosody,jicofo,jvb,jigasi,jibri}`

## Configuring Jitsi

1. `nano .env`
2. make sure it uses an unused port  
`HTTP_PORT=8000`
3. set timezone  
`TZ=Europe/Berlin`
4. set the later used public URL  
`PUBLIC_URL=https://meet.eolab.de`

## Configuring NGINX

1. `sudo nano /etc/nginx/sites-available/eolab.de`
2. make sure there is a redirect from HTTP to https (port 80 to 443)
3. add this to the top

```
upstream jitsi {  
    server localhost:8000;  
}
```

change the port if needed

1. add this to the bottom

```
server {  
    listen 443 ssl http2;  
    listen [::]:443 ssl http2;  
    server_name meet.eolab.de;  
  
    ssl_certificate /etc/letsencrypt/live/meet.eolab.de/fullchain.pem;  
    ssl_certificate_key /etc/letsencrypt/live/meet.eolab.de/privkey.pem;  
    include snippets/ssl-params.conf;  
  
    add_header Strict-Transport-Security "max-age=31536000; includeSubdomains;  
preload";  
    add_header X-Xss-Protection "1; mode=block";  
    add_header X-Content-Type-Options nosniff;  
    add_header Referrer-Policy same-origin;  
    proxy_cookie_path / "/; HTTPOnly; Secure";  
    add_header Expect-CT "enforce, max-age=21600";  
    add_header Feature-Policy "payment none";  
  
    keepalive_timeout 70;  
    sendfile on;  
    client_max_body_size 0;  
  
    gzip on;  
    gzip_disable "msie6";  
    gzip_vary on;  
    gzip_proxied any;  
    gzip_comp_level 6;  
    gzip_buffers 16 8k;  
    gzip_http_version 1.1;  
    gzip_types text/plain text/css application/json application/javascript  
text/xml application/xml application/xml+rss text/javascrip$  
  
    location / {  
        log_not_found off;  
        proxy_cache_valid 200 120m;
```

```
    proxy_set_header    Host      $http_host;
    proxy_set_header    X-Real-IP $remote_addr;
    proxy_set_header    X-Forwarded-For $proxy_add_x_forwarded_for;
    proxy_set_header    X-Scheme $scheme;
    proxy_pass http://jitsi/;
}

location ~ ^/colibri-ws/([a-zA-Z0-9-\.]+)/(.*) {
    tcp_nodelay on;
    proxy_http_version 1.1;
    proxy_set_header Upgrade $http_upgrade;
    proxy_set_header Connection "upgrade";
    proxy_pass http://jitsi/colibri-ws/$1/$2$is_args$args;
}

location /xmpp-websocket {
    tcp_nodelay on;
    proxy_http_version 1.1;
    proxy_set_header Upgrade $http_upgrade;
    proxy_set_header Connection "upgrade";
    proxy_set_header Host $host;
    proxy_pass http://jitsi/xmpp-websocket;
}
}
```

make sure to change:

- server\_name
- ssl\_certificate and ssl\_certificate\_key

1. Save and quit the file

2. `sudo systemctl restart nginx`

From:

<https://student-wiki.eolab.de/> - HSRW EOLab Students Wiki

Permanent link:

[https://student-wiki.eolab.de/doku.php?id=user:jan001:jitsi\\_docker&rev=1617288668](https://student-wiki.eolab.de/doku.php?id=user:jan001:jitsi_docker&rev=1617288668)

Last update: **2023/01/05 14:38**

